

PandaADCP-DR-600K

200m, 1000m, 3000m, 6000m direct - reading ADCP



TECHNICAL SPECIFICATIONS

Brand	PandaADCP		
Working Frequency	600kHz		
Operating Mode	Direct-Reading		
Batteries	No Batteries		
Water Profiling Range (Broadband / Narrowband)	55m/70m		
Bottom Track Range	110m		
Velocity Accuracy	$\pm 0.3\% \pm 3\text{mm/s}$		
Velocity Resolution	1mm/s		
Velocity Range	$\pm 5.0 \text{ m/s}$ (Default); $\pm 20.0 \text{ m/s}$ (Maximum)		
Number of Depth Cells	1 - 255		
Ping Rate	2Hz(typical)		
Depth Cell Size(High Precision Mode)	0.5 - 4m		
Depth Cell Size(Long Range Mode)	4m		
Echo Intensity Dynamic Range	100dB		
Echo Intensity Precision	$\pm 1.5\text{dB}$		
Standard Profiling Modes	High resolution water profiling, Fast sampling		
Beam Angle	20°		
Beam Width	3.5°		
Beam Configuration	4-beams, convex		
Internal Memory	64 GB Micro SD Card		
Communications	RS - 232 or RS - 422		
Sensor (Water Temperature)	Range: -5°C to 45°C , Accuracy: $\pm 0.1^{\circ}\text{C}$		
Sensor (Pressure	Range: according to depth rate, Accuracy: $\pm 0.25\%$ Range		
Sensor (Compass)	Range: 0° - 360° , Accuracy: 2° RMS, Resolution: 0.01°		
Sensor (Tilt)	Range: Roll $\pm 180^{\circ}$ Pitch $\pm 90^{\circ}$, Accuracy: $< 0.1^{\circ}$ RMS, Resolution: 0.01°		
Operating Temperature	-5°C to 45°C		
Storage Temperature (Without Batteries)	-30°C to 60°C		
Power Input	20V - 50V, 5A		
Casing	Titanium alloy		
Weight(In air/In water)	2.4 kg/1.4 kg (200m/1000m)	3.8 kg/2.8 kg (3000m)	4.8 kg/3.6 kg (6000m)
Dimension(Exclude top connector)	$\Phi 130 \text{ mm} \times 148 \text{ mm}$ (200m/1000m)	$\Phi 145 \text{ mm} \times 150 \text{ mm}$ (3000m)	$\Phi 145 \text{ mm} \times 160 \text{ mm}$ (6000m)
Available Options	External battery case, Bottom tracking, AC/DC power converter		

China Sonar (Hangzhou) Technology Co., Ltd.

Website: <https://china-sonar.com/>

E-mail: sales@china-sonar.com

Specifications subject to change without notice.

© 2025China Sonar (Hangzhou) Technology Co., Ltd., Inc. All rights reserved. Rev. February 2025